

DECLARATION OF PERFORMANCE

PFPO9EN003

1. Unique identification code of the product-type:

JUTAFOL REFLEX Light

2. Intended use:

*Flexible sheets for waterproofing - Plastic and rubber vapour control layers -
Definitions and characteristics*

3. Producer:

*Juta a.s., Dukelská 417, 544 15 Dv r Králové nad Labem, Czech Republic
Tel.: +420 499 314 211, Fax: +420 499 314 210
www.juta.cz*

4. Authorised representative:

not listed

5. POSV Systems:

system 3

6. Harmonised Standard:

EN 13984:2013

Identification number of the notified body:

*Institut pro testování a certifikaci a.s., Divize CSI - Centrum stavebního
inženýrství. Pražská 16, Praha 10, 102 21
Oznámený subjekt 1390*

7. Declared properties:

Essential characteristics	Performance				Harmonised technical specification
	Units	Nominal value	Tolerance		
Reaction to fire	[class]	E	-	-	EN 13984:2013
Water tightness	-	conforming	-	-	
Water vapour transmission properties (Sd)	[m]	200	-60	+60	
Determination of resistance to impact	-	npd	-	-	
Joint strength	[N]	npd	-	-	
Maximum tensile force MD/CMD	[N/50mm]	>230 / >230	-	-	
Resistance to tearing MD/CMD	[N]	>110 / >110	-	-	
Resistance to alkali	-	npd	-	-	
Durability of water vapour resistance against ageing	-	conforming	-	-	
Dangerous substances		npd			

Notes: MD - Machine Direction, CMD - Cross Machine Direction, npd - no performance determined;

8. Relevant technical documentation / specific technical documentation:

not issued

9. Properties of the above stated product are in compliance with the set of declared properties. In accordance with Regulation (EU) No. 305/2011, this properties declaration is issued under the sole responsibility of the producer mentioned above.

Signed for and on behalf of the manufacturer by:

Ing. Jiří Hlavatý
Statutory director

In Dvůr Králové nad Labem, 19.03.2019

