

## DECLARATION OF PERFORMANCE

*PFM32EN003*

1. Unique identification code of the product-type:

*JUTATOP*

2. Intended use:

*Flexible sheets for waterproofing - Definitions and characteristics of underlays - Part 1:  
Underlays for discontinuous roofing*

3. Producer:

*JUTA a.s., Dukelská 417, 544 15 Dv r Králové nad Labem, eská republika  
Tel.: +420 499 314 211, Fax: +420 499 314 210  
www.juta.cz*

4. Authorised representative:

*not listed*

5. POSV Systems:

*system 3*

6. Harmonised Standard:

*EN 13859-1:2010*

Identification number of the notified body:

*Institut pro testování a certifikaci a.s., Divize CSI - Centrum stavebního  
inženýrství. Pražská 16, Praha 10, 102 21  
Oznámený subjekt 1390*

7. Declared properties:

Essential characteristics	Performance			Harmonised technical specification	
	Units	Nominal value	Tolerance		
Reaction to fire	[class]	B	-	-	EN 13859-1:2010
Resistance to water penetration	[class]	W1	-	-	
Resistance to water penetration after artificial ageing	[class]	W1	-	-	
Water vapour transmission properties (Sd)	[m]	0,02	-0,01	+0,04	
Tensile properties: Maximum tensile force MD / CMD	[N/50mm]	360 / 240	-60 / -40	+60 / +50	
Max tensile force after artificial ageing MD / CMD	[N/50mm]	350 / 230	-60 / -40	+60 / +50	
Tensile properties: Elongation MD / CMD	[%]	25 / 25	-10 / -10	+15 / +15	
Elongation after artificial ageing MD / CMD	[%]	23 / 23	-9 / -9	+15 / +15	
Resistance to tearing MD / CMD	[N]	160 / 190	-40 / -50	+50 / +60	
Flexibility at low temperature	[°C]	-40	-	-	
Dangerous substances		npd			

Notes: \* - according to requirement, MD - Machine Direction, CMD - Cross Machine Direction, npd - no performance determined

8. Relevant technical documentation / specific technical documentation:

*not issued*

9. Properties of the above stated product are in compliance with the set of declared properties. In accordance with Regulation (EU) No. 305/2011, this properties declaration is issued under the sole responsibility of the producer mentioned above.

Signed for and on behalf of the manufacturer by:

Ing. Jiří Hlavatý  
Statutory director

In Dvůr Králové nad Labem, 05.05.2020

